


# Mitel 6930w IP Phone



Powerful, Wi-Fi equipped IP phone designed for the power user

## Key Features

- 4.3" (480x272 pixel) color display
- Wi-Fi – dual band 802.11 a/b/g/n
- Bluetooth 5.2
- Mitel PCLink
- MobileLink mobile device integration
- Mobile phone charging point
- Support for optional Cordless handset
- Enhanced full-duplex speakerphone
- Highly customizable via broad array of optional add-on accessories



The Mitel 6930w is designed for power users who need a phone that can be tailored to their specific communication needs. The 6930w provides flexible network connectivity options including wired Ethernet and built-in Wi-Fi to facilitate installation in work-at-home and corporate environments. The 6930w's first-of-its-kind PCLink feature turns your phone into a high quality audio device for PC based video collaboration. PCLink enables seamless handling of both phone calls and PC audio through a single easy-to-use device. By connecting the phone to your favorite video collaboration solution you now have one centralized, high quality audio device for all communication. The enhanced full-duplex speakerphone and optional accessories like the Mitel integrated DECT cordless or H-Series headset and Bluetooth cordless handset give you the flexibility you need fit with the way you work.

## PCLink

PCLink solves the challenge today's home-based workers face day-in and day-out – how to effectively manage two necessary but independent communications modes: traditional phone calls and PC based collaboration. PCLink gives you the best of both worlds in a single, familiar, easy-to-use, high quality audio device – the 6930w IP Phone. Using PCLink, you are no longer forced to use two separate audio accessories, one for your phone and one for your PC – all communications are managed by the 6930w. The 6930w frees you to work handsfree using the high-quality speakerphone or the optional integrated cordless DECT headset, that allows you to roam about your house or office floor thanks to its exceptional operating range.

## MobileLink Mobile Integration

The 6930w IP Phone's MobileLink mobile device integration seamlessly marries mobile phone call audio and both contact and call log information with the desktop phone. Calls to the mobile phone can be answered on the 6930w just like any other call leveraging the superior audio performance and ergonomics of the 6930w. Mobile Phone contacts and call history are automatically synchronized with the 6930w allowing access to the same information on either device. A powered USB port suitable for charging a mobile phone is also built into the 6930w.

## Flexible Headset Options

The Mitel 6930w offers a unique, physically integrated DECT cordless headset option that provides unparalleled integration between phone and headset. The 6930w also provides BT and USB headset support and features an innovative analog headset port that uniquely provides dual support for DSHG and modular 4-pin headset connections.

## Feature Keys

- 12 programmable keys with paging that enables up to 72 Lines, Speed Dials and Telephony functions\*
- 5 context sensitive keys with paging support\*
- 4-way navigation key

## Audio and Codecs

- Hearing aid compatible (HAC) handset
- Full-duplex high-quality speakerphone
- Codecs (supported codecs differ based on call manager platform/cloud service):
  - » G.711, G.729, G.722 G
  - » 722.1 (MiNet Only)
  - » G.726, iLBC AMR, G.722.2 AMR-WB (SIP Only)

## Display and Indicators

- 4.3" QVGA (480x272 pixel) color display
- Intuitive graphical user interface and navigation menus
- Adjustable screen brightness for user comfort in different lighting environments
- Programmable key indicators
- Dedicated LED for call and message waiting and Mobile Device Connect indication

## Protocol Support

- SIP protocol support
  - Mitel and 3rd Party call control
- Mitel IP (MiNet) protocol support

## Connectivity

- Wi-Fi – dual band (2.4GHz / 5GHz) 802.11 a/b/g/n
- Dual Gigabit Ethernet ports - LAN + PC
- Bluetooth (BT) version 5.2
- Powered USB 2.0 Host port (500mA)
- Sidecar expansion port
- Dedicated 4-pin modular headset port convertible to DSHG capable headset port

## Integration

- *PCLink – use phone for PC audio via BT*
- *MobileLink*
  - » *Mobile pairing via BT*
  - » *Mobile Call Audio via desk phone*
  - » *Mobile Contact Sync*
  - » *Mobile Call Log Sync*
- *Mobile Charging (USB port)*
- *Support for Mitel Teleworker Solution, Automatic Call Distribution (ACD) agent and supervisor, hot desking, and resiliency*
- *Secure encrypted voice communication*
- *Quality of Service support – IEEE 802.1 p/Q VLAN and priority tagging*
- *IEEE 802.1x authentication support*

## Powering

- *Designed for power conservation*
- *Accepts IEEE 802.3az Energy Efficient Power over Ethernet (POE)*
- *POE Class 3 with automatic POE class change on Expansion Module Installation*
- *Supports local power via 48V wall adapter*

## Power Consumption

- *Idle 1.3w      Typical 3.4*

## Environmental / Regulatory Standards

### EMC

#### **CANADA:**

*ICES-003 (CLASS B)*

*RSS-247*

#### **USA:**

*CFR Title 47, Part 15 Subpart B (CLASS B)*

*FCC Part 15 Subpart C*

#### **EUROPE:**

*EN55024 (EU)*

*EN55032, Class B*

*EN 301-489-1-17*

*EN 300 328*

*EN 50360*

#### **AUSTRALIA / NEW ZEALAND:**

*AS/NZS CISPR 22*

### Safety

#### **CANADA:**

*CAN/CSA C22.2 No. 60950-1*

#### **USA:**

*UL 60950-1*

#### **EUROPE:**

*EN 60950-1*

#### **AUSTRALIA / NEW ZEALAND:**

*AS/NZS 60950-1*

### Telecom

#### **CANADA:**

*CS03 Part V (Hearing Aid Compatible)*

#### **USA:**

*FCC part 68 (CFR 47) (Hearing Aid Compatible)*

#### **AUSTRALIA / NEW ZEALAND:**

*PTC220*

*AS/CA S004*

*AS/ACIF, S040*

## Temperature Ratings

- *Operational:*
  - » *Operational +4°C to +49°C*
  - » *Humidity 34% at +49°C 95% at +29°C*
- *Storage:*
  - » *Operational -30°C to +70°C*
  - » *Humidity 15% at +70°C 95% at +29°C*

## Other

- *MTBF Rate: 40 years*
- *Size (L x W x H): 9.3 in x 5.9 in x 7.5 in (23.5cm x 15cm x 19cm)*
- *Weight: 2.4 lbs or 1.08 kg*

*Note: Maximum number of functions varies by call manager platform*